


TP 1677

250 ML (5) SS

Dimensions



Shape :	Square
L-1	120,5 mm +/- %1
L-2	120,5 mm +/- %1
H-1	41,3 mm +/- %1

Volume

Brimful Volume :	412 cc
Iso Volume :	273 cc

Weight

Weight container / pot	14 gr. +/- 1 gr.
Weight standard lid	

Performance

Hot filling	85-95 ° C
Hot temperatures	The material chosen has a very good heat resistance and the pails are suitable for hot filling. Notably, plastic pails become flexible when subjected to hot filling temperatures and care must be taken in relation to stacking immediately after hot filling. The TP 1677 must be tested by the customer with the actual product before approval for use at hot temperatures.

Handle

Available handle	-	Handle type	Flexible Plastic
------------------	---	-------------	------------------

Closure System

Lid type options	Standard Lid
Closure type	Sealing lid
Protective collar	Yes
Tamper Evidence Type	Tamper Evidence tap



Decoration

Decoration Available :	<input type="checkbox"/> Offset	Decoration area offset	-
	<input checked="" type="checkbox"/> IML	Decoration area IML(Pail)	38 mm x 400 mm
		Decoration area IML(Lid)	-

Packaging (Per bucket)

	1000 X 1200
On pallet	8.400 pcs.
Pallet Height	250 cm.
Amount of pallets per 40" HC	21 pallet
Amount of pcs per 40" HC	176.400 pcs.
Amount of pallets per truck	26 pallet
Amount of pcs per truck	218.400 pcs.

Raw Material

Quality Specifications



ISO 9001 - 2008
ISO 22000 - 2005

